

Item	Amount (m ²)	Product/service	Prize per unit (€)	Total (€)														
		<p>Sandwich wall panel Thermowall Kombi</p> <p>with panel joint for visible fixing, external and internal side galvanised and coated steel sheet with polyurethane rigid foam core. Cover width 1000 mm</p> <p>Class of building material: B-s2-d0 low flammable according to DIN EN 13501</p> <p><u>External sheet:</u> t=0,60 mm, S-profiled micro-profiled 25 µm polyester, standard colours corrosion protection class III</p> <p><u>Internal sheet:</u> t=0,45 mm, S-profiled with stucco embossing DU polyester, MC 9002 corrosion protection class II</p> <table data-bbox="336 943 1137 1189"> <thead> <tr> <th><u>Panel thickness (s):</u></th> <th><u>Thermal conductivity (U):</u></th> </tr> </thead> <tbody> <tr> <td>60 mm</td> <td>0,413 W/m²K</td> </tr> <tr> <td>80 mm</td> <td>0,307 W/m²K</td> </tr> <tr> <td>100 mm</td> <td>0,244 W/m²K</td> </tr> <tr> <td>120 mm</td> <td>0,203 W/m²K</td> </tr> <tr> <td>150 mm</td> <td>0,162 W/m²K</td> </tr> <tr> <td>200 mm</td> <td>0,121 W/m²K</td> </tr> </tbody> </table> <p><i>U values with joint coefficient (Ψ) according to DIN EN 14509</i></p> <p>Delivery and installation vertically on steel-or wooden support construction horizontally on steel-or wooden support construction with HTU-rails</p> <p>according to approval, the installation guidelines of Metecno Bausysteme GmbH and the technical regulations of the IFBS. Use only stainless steel screws with EPDM-washers. Any necessary cuttings are to be taken into account.</p> <p>Installation height: m</p> <p>Panel length: m</p>	<u>Panel thickness (s):</u>	<u>Thermal conductivity (U):</u>	60 mm	0,413 W/m ² K	80 mm	0,307 W/m ² K	100 mm	0,244 W/m ² K	120 mm	0,203 W/m ² K	150 mm	0,162 W/m ² K	200 mm	0,121 W/m ² K		
<u>Panel thickness (s):</u>	<u>Thermal conductivity (U):</u>																	
60 mm	0,413 W/m ² K																	
80 mm	0,307 W/m ² K																	
100 mm	0,244 W/m ² K																	
120 mm	0,203 W/m ² K																	
150 mm	0,162 W/m ² K																	
200 mm	0,121 W/m ² K																	

as of November 2019