

Item	Amount (m ²)	Product/service	Prize per unit (€)	Total (€)																		
		<p>Sandwich roof panel G4</p> <p>external and internal side galvanised and coated steel sheet with polyurethane rigid foam core. Cover width 1000 mm</p> <p>Class of building material: B-s2-d0 low flammable according to DIN EN 13501</p> <p><u>External sheet:</u> t=0,60 mm, trapeze-profile, distance between ribs: 333 mm, 25 µm polyester, standard colours corrosion protection class III</p> <p><u>Internal sheet:</u> t=0,45 mm, S-profiled without stucco-embossing DU polyester, MC 9002 corrosion protection class II</p> <table border="0"> <tr> <td><u>Core-/Panel thickness (s/d):</u></td> <td><u>Thermal conductivity (U):</u></td> </tr> <tr> <td>30/68 mm</td> <td>0,798 W/m²K</td> </tr> <tr> <td>40/78 mm</td> <td>0,598 W/m²K</td> </tr> <tr> <td>50/88 mm</td> <td>0,499 W/m²K</td> </tr> <tr> <td>60/98 mm</td> <td>0,399 W/m²K</td> </tr> <tr> <td>80/118 mm</td> <td>0,299 W/m²K</td> </tr> <tr> <td>100/138 mm</td> <td>0,240 W/m²K</td> </tr> <tr> <td>120/158 mm</td> <td>0,199 W/m²K</td> </tr> <tr> <td>150/188 mm</td> <td>0,160 W/m²K</td> </tr> </table> <p><i>U values with joint coefficient (Ψ) according to DIN EN 14509</i></p> <p>Delivery and installation on steel- or wooden support construction according to approval, the installation guidelines of Metecno Bausysteme GmbH and the technical regulations of IFBS. Use stainless steel screws with EPDM-washers only. Sealing tapes, saddle caps and any necessary cuttings are to be taken into account.</p> <p>Roof pitch:</p> <p>Eaves height: m</p> <p>Panel length: m</p>	<u>Core-/Panel thickness (s/d):</u>	<u>Thermal conductivity (U):</u>	30/68 mm	0,798 W/m ² K	40/78 mm	0,598 W/m ² K	50/88 mm	0,499 W/m ² K	60/98 mm	0,399 W/m ² K	80/118 mm	0,299 W/m ² K	100/138 mm	0,240 W/m ² K	120/158 mm	0,199 W/m ² K	150/188 mm	0,160 W/m ² K		
<u>Core-/Panel thickness (s/d):</u>	<u>Thermal conductivity (U):</u>																					
30/68 mm	0,798 W/m ² K																					
40/78 mm	0,598 W/m ² K																					
50/88 mm	0,499 W/m ² K																					
60/98 mm	0,399 W/m ² K																					
80/118 mm	0,299 W/m ² K																					
100/138 mm	0,240 W/m ² K																					
120/158 mm	0,199 W/m ² K																					
150/188 mm	0,160 W/m ² K																					

